



Key features- SWI-WINTAG (Windshield Tag)

- Windshield adhesive tag for vehicle glass installation only.
- Frequency: Operates on 865–868 MHz in EU frequency band.
- Reading Range: Reads accurately up to 15 meters in distance.
- Writing Range: Can be written up to 4 meters reliably.
- Tamper Proof: Slits destroy tag if removed or tampered.
- Adhesive: Pressure-sensitive, low-energy adhesive for strong windshield sticking.
- Material: Encapsulated in white polyester, thickness 0.002 inches.
- Dimensions: Tag size is 4.5 x 1.5 inches.
- Environment: Works between -20°C to +70°C without failure.
- Memory: 96-bit user memory with Secure MarkID™ protection features.

SWI-WINTAG



Technical Specifications

Specification	Details
Type	Windshield adhesive tag for vehicle glass installation only.
Frequency	Operates on 865–868 MHz in EU frequency band.
Reading Range	Reads accurately up to 12 meters in distance.
Writing Range	Can be written up to 4 meters reliably.
Tamper Proof	Slits destroy tag if removed or tampered.
Adhesive	Pressure-sensitive, low-energy adhesive for strong windshield sticking.
Material	Encapsulated in white polyester, thickness 0.002 inches.
Dimensions	Tag size is 4.5 x 1.5 inches.
Environmental Range	Works between -20°C to +70°C without failure.
Memory & Protection	96-bit user memory with Secure MarkID™ protection features.

